

rustdesk

ein Netzwerk anlegen mit dem Namen `rustdesk`

ein Volume anlegen mit dem Namen `rustdesk`

```
version: '3.8'
```

```
services:
```

```
  hbbs:
```

```
    container_name: rustdesk-hbbs
```

```
    hostname: rustdesk-hbbs
```

```
    image: rustdesk/rustdesk-server:latest
```

```
    restart: unless-stopped
```

```
    networks:
```

```
      - rustdesk
```

```
  ports:
```

```
    - "21115:21115"
```

```
    - "21116:21116"
```

```
    - "21116:21116/udp"
```

```
    - "21118:21118"
```

```
  depends_on:
```

```
    - hbbr
```

```
  command: hbbs -r <EURE.DYNDS.DE>:21117
```

```
  volumes:
```

```
    - rustdesk:/root
```

```
  environment:
```

```
    - TZ=Europe/Berlin
```

```
  hbbr:
```

```
    container_name: rustdesk-hbbr
```

```
    hostname: rustdesk-hbbr
```

```
    image: rustdesk/rustdesk-server:latest
```

```
    restart: unless-stopped
```

```
    networks:
```

```
      - rustdesk
```

```
  ports:
```

```
    - "21117:21117"
```

```
    - "21119:21119"
```

command: hbbr

volumes:

- rustdesk:/root

environment:

- TZ=Europe/Berlin

networks:

rustdesk:

external: true

volumes:

rustdesk:

external: true

Revision #1

Created 30 March 2023 19:40:25 by Remo

Updated 30 March 2023 19:42:21 by Remo