

# vaultwarden

vor dem Ausrollen noch ein Volume mit dem Namen `vaultwarden` anlegen

```
version: '3.8'
```

```
services:
```

```
  vaultwarden:
```

```
    container_name: vaultwarden
```

```
    hostname: vaultwarden
```

```
    image: vaultwarden/server:latest
```

```
    restart: unless-stopped
```

```
    security_opt:
```

```
      - no-new-privileges:true
```

```
    networks:
```

```
      - proxy
```

```
    ports:
```

```
      - "8080:80"
```

```
    volumes:
```

```
      - vaultwarden:/data
```

```
    environment:
```

```
      - TZ=Europe/Berlin
```

```
      - WEBSOCKET_ENABLED=true # Enable WebSocket notifications.
```

```
      - ADMIN_TOKEN=xxxxxx[ ]# <-- mit eigenem Token anpassen
```

```
      - DOMAIN=https://xxx.xxx.xx[ ]# <-- mit eigener Domain anpassen
```

```
      - SIGNUPS_ALLOWED=false
```

```
      - SIGNUPS_VERIFY=true
```

```
volumes:
```

```
  vaultwarden:
```

```
    external: true
```

```
networks:
```

```
  proxy:
```

```
    external: true
```

---

Revision #2

Created 23 March 2023 22:49:22 by Remo

Updated 23 March 2023 22:57:10 by Remo